



Hitools@Identify
Hitools@Security

HITOOLS ACCESS
+33(0)2.43.28.15.04

44 rue des Mûres - 92160
ANTONY - FRANCE
info@hitools-access.com
www.hitools-access.com





Functional Specifications:

RFID Protocol:	EPC Class1 Gen2, ISO18000-6C
Frequency:	(US) 902-928MHz, (EU) 865-868MHz
IC type:	Alien Higgs-3
Memory:	EPC 96bits (Up to 480bits) , USER 512bits, TID64bits
Write Cycles:	100,000times
Functionality:	Read/wirte
Data Retention:	Up to 50 Years
Applicable Surface:	Metal Surfaces
Read Range :	Up to 4.7M - (US) 902-928MHz, on metal
(Fix Reader:ThingMagic FU-M6-E, 30dBm)	Up to 4.5M - (EU) 865-868MHz, on metal
Read Range :	Up to 2.3M - (US) 902-928MHz, on metal
(Handheld Reader: Moto 310, 30dBm)	Up to 2.0M - (EU) 865-868MHz, on metal
Warranty:	1 Year


Physical Specification:

Size:	36x13mm, (Hole: D2mm)
Thickness:	3.5mm
Material:	FR4 (PCB)
Colour:	Black (Red, Blue, Green, White)
Mounting Methods:	Adhesive, Screw






OPP3613U1:



OPP3613E1:



Environmental Specification:

IP Rating:	IP68
Storage Temperature:	-40°C to +150°C
Operation Temperature:	-40°C to +100°C
Certifications:	RoHS Approved, CE Approved

Order information:

OPP3613U1	(US) 902-928MHz,
OPP3613E1	(EU) 865-868MHz

