

DESFire®/Mifare® Reader with Keypad

DF750 / DF760 & DF750K / DF760K series are available for user's end configuration by applying MIFARE® sector and MIFARE® DESFire® technology. They can be configured to read MIFARE® DESFire cards with MAD3 or MIFARE® MAD1/MAD2 sector standard in a Mifare® application open system, or can be configured to read the user-defined sector data (Non-MAD) in a user defined closed system.



DF750/DF760

DF750K/DF760K



Indoor/outdoor Design	Weather resistant with metal keypad. Protection Classification: IP66
Security	mutual three pass authentication, DES & 3DES MACing / Encipherment.
3 in 1 Output Interface	Wiegand (Default) / ABA TK2 / RS232 or RS485 Wiegand output is selectable from 1 bits to 128 bits RS232/RS485 output packet can be set with Header, Reader ID and trailer
LED/Buzzer	Internal LED and buzzer are configurable or control with RS232 commands or wires.
Multi-Applications	Supports MIFARE MAD1/MAD2, DESFire® Files standard and customer MAD-AID setting. Supports Non-MAD format with user-defined sector number. <small>* DF750K/DF760K: Reads Mifare® DESFire or MIFARE® Classic cards with pass code.</small>
Multi-Readers	Can be set with a Reader ID number for multi-unit communication
Certification	R&TTE / FCC
Keypad	DF750K/DF760K: metal keypad with 4*3 Keys and output 4/6/8 bits wiegand/ASCII code or Buffering

Specifications:

Security	DES & 3DES MACing / Encipherment
Interface	DF750/DF750K: RS232 DF760/DF760K: RS485
Power Requirements	7.5 V~24V *A regulated power is recommended
Card type	MIFARE® DESFire (4K/8K for MAD3), MIFARE® Classic (1K/4K for MAD1/MAD2)
Maximum reading distance	Mifare:Up to 11 cm (MFA01A) ; DESFire:Up to 6 cm (CRD-T0011) @12V
Frequency	13.56 MHz standard
Card format	MAD1 / MAD2, and MAD3
Audio / Visual Indication	Internal LED and Buzzer
Dimensions	112.3 L x 96W x 22D mm
Housing material	DF750/DF760: ABS housing DF750K/DF760K: ABS housing/Metallic keys
Environment	Operating temperature 0 °C ~ +60 °C ; Operating relative humidity 10~90%
Protection Classification	IP66
Certification	R&TTE / FCC

* Specification is subject to change without notice.

Applications:

- Access Control System.
- Time attendance.
- Guest registration system.
- Authorization Identification.
- Identity Authentication.

Company profile:

Giga-Tms was established in Taiwan in 1987 as a magnetic technology products manufacturer. Ten years later, as soon as the company's CEO noticed the new RFID technique, he immediately foresaw its potential and engaged the R&D group in RFID. Now with its 21 years experience, Giga-Tms owns not only proven RFID techniques of superior standard but also makes reliable products for long life. Giga-Tms always takes into account providing flexible and customized services to every customer. Although based in Taiwan, Giga-Tms exports 90 percent of the annual production mostly to worldwide market. Now in its 21 year, Giga-Tms is looking to strength its image through increased advertising, while remaining faithful to its principles: prioritize the customer.

GIGA-TMS INC.

8F, NO. 31, LANE 169, KANG-NING STREET,
HSI-CHIH. TAIPEI COUNTY, TAIWAN
Tel: 886-2-26954214 Fax: 886-2-26954213
<http://www.gigatms.com.tw/>
Email: promag@gigatms.com.tw
promag@ms24.hinet.net